



#4000-G Gas Machine



18 HP Gas Engine

Maximize your production (open-blow) with our #4000-G **all-fiber** (airlock) machine, featuring a large 14 inch (35.5cm.) diameter by 14 inch (35.5cm.) long airlock. Designed for low maintenance and high production, the #4000-G provides large hopper capacity and easy loading, while offering simple rugged performance. The #4000-G is intended to function as a truck mount machine for the **professional contractor**.

MATERIAL PRODUCTION RATE

MATERIAL	lbs/hr (kg/hr)
CELLULOSE	4000 (1814)
FIBERGLASS	1500 (680)

lbs/hr (kg/hr) rating with 150ft. (45.8m.) of 4" (10.2cm.) hose at 16ft. (4.9m.) elevation
Product density and variable blowing conditions will affect production rate.

WEIGHT

1460 lbs. (662 kg.)

DIMENSIONS

43"W x 69"D x 83"H
(109cm. W x 175cm. D x 211cm. H)

HOPPER CAPACITY

62 cu. ft. (1.70 m³)

AIRLOCK

14" x 14" diameter (35.5cm. x 35.5cm. diameter)
4" (10cm.) outlet for blowing hose

STANDARD FEATURES AND BENEFITS

Mechanical

- Positive Displacement Blower Provides - 150 CFM @ 5psi
- Modular component design for easy troubleshooting and maintenance
- Safety guards provide operator safety
- 62 cu. ft. (1.70 m³) hopper provides large capacity
- Three (3) stainless steel agitators enhance the condition of fibers with no corrosion
- Removable all steel airlock allows quick access to airlock for replacing seals
- Shredder assembly increases production and material conditioning
- Gear reducer (3070 in./lb. torque) provides durable direct drive transmission for the toughest blowing materials
- Extra heavy, nickel plated #50 chain with hardened steel sprockets provides a rugged, corrosion/abrasion resistant drive system
- Check valve protection and pressure relief on the positive displacement blower
- 18 Hp gas engine

Electrical

- Operator safety/Hazard response features: pre-alarm buzzer, emergency kill switch, manual override at the machine, 150 ft. (46m.) of remote control cord





Pumps

- 348B MP-20 Pump & Motor (Belt Drive)
- 348D M-3 Pump & Motor (Direct Drive)

Hose

- H319 Flexhose - 3" x 50'
- H329 Flexhose - 3 1/2" x 50'
- H330 Flexhose - 4"x 50'

Hose Reels

- 323 Hose reel - 15.5" (Holds 200ft. 3/8" hose)
- 328 Hose reel - 36" (Holds 150 ft. 3" hose)
- ST328 Hose reel - Wall mount 36"
- ST329 Hose reel- Wall mount 44"
- 349-A Hose reel - Wall mount 90" (Holds 200 ft.)
- KS333-A Hose reel - Wall mount 90" (Holds 150 ft.)

Spray Equipment

- 347 Glue Kit
- 349WC2-2-M 2" Wall Cavity Nozzle (Less Tips)
- 349WC2.5-2-M 2 1/2" Wall Cavity Nozzle (Less Tips)
- 349WC3-2-M 3" Wall Cavity Nozzle (Less Tips)
- QVVA2501 Wall Cavity Spray Tips (.026 opening)
- QVVA25015 Wall Cavity Spray Tips (.031 opening)
- QVVA2502 Wall Cavity Spray Tips (.036 opening)
- QVVA2503 Wall Cavity Spray Tips (.043 opening)
- QVVA4002 Wall Cavity Spray Tips (.036 opening)
- 349B-A Wall Scrubber 27" (Standard Parallel)
- 349B-B Wall Scrubber 27" (Extended Parallel)
- 349B-C Wall Scrubber 27" (Extended Vertical)
- 349B-D Wall Scrubber 18" (Standard Parallel)
- 348B-E Wall Scrubber 18" (Extended Parallel)

Reducers & Nozzles

- 355 Reducer tube - 4" to 3"
- 358 Reducer tube - 3" to 2"
- 359 Reducer tube - 3" to 2 "
- 362 Reducer tube - 4" to 3 1/2 "



Connector Tubes

- 380 Connector - (steel) 3" x 5"
- 383 Connector - (steel) 3 " x 5"
- 381 Connector - (steel) 4 1/2" x 5"

Hose Accessories

- 339A Clamp for 3" hose
- 339B Clamp for 3 1/2" hose
- 340 Clamp for 4" hose

Optional Equipment

- 356 Wireless Remote (120VAC)
- 360 Wireless Remote (12VDC)



Krendl Machine Company
Greg Gossman-Sales Manager
ggossman@krendlmachine.com
1-800-459-2069
Fax: 419-695-9301