



5200



Avail. - PTO & Diesel

Maximize your production (open-blow) with our #5200 **all-fiber** (airlock) machine, featuring a large 14 inch (35.5cm.) diameter by 18 inch (45.7cm.) long airlock. Designed for low maintenance and high production, the #5200 provides large hopper capacity and easy loading, while offering simple rugged performance. The #5200 is intended to function as a truck mount machine for the **professional contractor** or for use in manufactured housing.

MATERIAL PRODUCTION RATE

MATERIAL	MACHINE w/positive displacement blower lbs/hr (kg/hr)
CELLULOSE	5200 (2358)
FIBERGLASS	2300 (1043)

lbs/hr (kg/hr) rating with 150ft. (45.8m.) of 4" (10.2cm.) hose at 16ft. (4.9m.) elevation
Product density and variable blowing conditions will affect production rate.

STANDARD FEATURES AND BENEFITS

WEIGHT

2120 lbs. (962 kg.)

DIMENSIONS

42"W x 82"D x 82"H
(106cm. W x 208cm. D x 208cm. H)

HOPPER CAPACITY

62 cu. ft. (1.70 m³)

AIRLOCK

18" x 14" diameter (45.7cm. x 35.5cm. diameter)
Slide Out Removable Airlock
4" (10cm.) outlet for blowing hose

BLOWERS/SIZES

Positive Displacement Blower provides
250 CFM @ 6psi

OPTIONAL EQUIPMENT

Wireless remote - Water tank enclosure

Mechanical

- Modular component design for easy troubleshooting and maintenance
- Safety guards provide operator safety
- 62 cu. ft. (1.70 m³) hopper provides large capacity
- Three (3) stainless steel agitators enhance the condition of fibers with no corrosion
- Removable all steel airlock allows quick access to airlock for replacing seals
- Shredder assembly increases production and material conditioning
- Gear reducer (3070 in./lb. torque) provides durable direct drive transmission for the toughest blowing materials
- Extra heavy, nickel plated #50 chain with hardened steel sprockets provides a rugged, corrosion/abrasion resistant drive system
- Check valve protection and pressure relief on the positive displacement blower
- 25 Hp diesel engine

Electrical

- Operator safety/Hazard response features: pre-alarm buzzer, main disconnect/power interruption shutdown, emergency kill switch, manual override at the machine, 150 ft. (46m.) of remote control cord
- 5000 running watt generator supplies auxiliary power for pump, lights, pump cabinet, etc. (on PTO & Diesel)